How do I add a new IP address to my server with Webmin?

Article Number: 49 | Rating: 1/5 from 3 votes | Last Updated: Wed, Aug 18, 2021 at 1:12 PM
Webmin, the web-based interface for administrating your Linux server, allows you to add more IP addresses to your server. In order to add more IP addresses, you must purchase them through your Heart Internet Customer Area. To add the new IP address: Open Webmin Go to Networking > Network Configuration > Network Interfaces Under ‘Interfaces Activated at Boot Time’, select ‘Add a new interface’ Since you are adding a virtual interface, the ‘Name’ will look like eth0:1 Set the IP address to your new IP address, and set the netmask correspondingly Set ‘Activate at boot?’ to ‘Yes’ Click ‘Create and Apply’ The new interface should be in both ‘Interfaces Active Now’ and ‘Interfaces Activated at Boot Time’ Click ‘Return to Network Configuration’ Click ‘Apply Configuration’ to ensure that the changes have been saved You should be able to ping the new IP address.Â It may take a minute or two to find the server, since this is the first time that the IP address is being used on your server.

Posted - Tue, Mar 3, 2015 at 3:52 PM.
Online URL:
https://www.heartinternet.uk/support/article/how-do-i-add-a-new-ip-address-to-my-server-with-webmin.html